

LA-UR-21-27061

Approved for public release; distribution is unlimited.

Title: High throughput tensile testing using femtosecond laser fabrication

technique

Author(s): Torrez, Avery Jude

Torrez, Avery Jude Harvey, Cayla Renee Lam, Sebastian R. Kim, Hyosim

Maloy, Stuart Andrew Gigax, Jonathan Gregory

Intended for: LANL Student Symposium

Issued: 2021-07-30 (rev.1)





High throughput tensile testing using femtosecond laser fabrication technique

Avery Torrez, Cayla Harvey, Sebastian Lam, Hyosim Kim, Stuart A. Maloy, Jonathan Gigax

August 3, 2021

LA-UR-21-27061



Main Purpose

To demonstrate that a high throughput method for fabrication and mechanical testing produces local and bulk-like results.




Mechanical Testing

Used to determine mechanical properties of a desired material

Common tests: Tensile, Hardness, Fatigue, Creep, etc.

Tensile tests are used to characterize stress and strain when loaded to failure

An in-house developed mechanical stage is used to test the samples in tension.



Sample Preparation Method

Step 1: Initial grinding/polishing to remove surface impurities


and scratches

Step 2: Subtractive fabrication method (Machining, Wire EDM,

Laser ablation, and Focused Ion Beam ablation)

FIB is time consuming and Machining/Wire EDM cause

significant damage at the desired scale (µm to mm)




What are femtosecond lasers?


Pulses with magnitude of 350 fs

Produces low heat affected zone (HAZ)


Efficient subtractive machining times for small (sub millimeter) features.

Flexible environments for ablation (in vacuum, water, etc.)





Grade 316L Stainless Steel Additively Manufactured Grade 91 Steel (AM91)



Results


Laser Fabricated Tensile Bars

Clean and accurate tensile bar cuts

Slight debris with no visible HAZ

Cross-sectional area of 0.015-0.020 mm

* This set of 11 took 35 minutes to fabricate (3:11 per sample)




Results

316L Results

19 Samples tested @ room temperature Time per sample: 5 minutes* Little variance to bulk 316L results 800 700 600 Stress (MPa) 200 100 0 0.2 0.4 0.6 0.8 Strain

AM91 Results





Discussion

Microstructure of AM91


Grain sizes of >40μm to <1μm

Variations in microstructure lead to variations in stress-strain responses along various print regions





Sub-microscale vs. Bulk Results for AM91



Conclusion

- Proves to decrease overall fabrication and testing time significantly and allowed for a large volume of data to be collected effortlessly
- Provides accurate stress-strain responses with homogenous microstructures like 316L.
- Provides boundary limits for strength and ductility for complex heterogeneous microstructures like AM91.



References

- [1] Cayla Harvey, Avery J. Torrez, Sebastian Lam, Hyosim Kim, Stuart A. Maloy, Jonathan Gigax, Demonstration of a high throughput tensile testing technique using femtosecond laser fabricated tensile bars in AISI 316 and additively manufactured grade 91 steel, Submitted to JOM (2021).
- [2] M.P. Echlin, M. Straw, S. Randolph, J. Filevich, T. M.Pollock, The TriBeam System: Femtosecond Laser ablation in situ SEM, Materials Characterization 100 (2015) 1-12.
- [3] R. Le Harzic, N. Huot, E. Audouard, C. Jonin, P. Laporte, Comparison of heat-affected zones due to nanosecond and femtosecond laser pulses using transmission electronic microscopy, Appl. Phys. Lett 80 (21) (2002).
- [4] P.B. Corkum, F Brunel, NK Sherman, T Srinivasan-Rao, Thermal Response of Metals to Ultrashort-Pulse Laser Excitation, Phys. Rev. Lett. 61 (1988).
- [5] S. Valette, E. Audouard, R. Le Harzic, N. Huot, P. Laporte, R. Fortunier, Heat affected zone in aluminum single crystals submitted to femtosecond laser irradiations, Applied Surface Science 239 (3-4) (2005) 381-386.
- [6] C. Momma, B.N. Chichkov, S. Nolte, F. von Alvensleben, A. Tunnerman, H. Welling, B. Wellegehausen, Short-pulse laser ablation of solid targets, Optics Communications 129 (1-2) (1996) 134-142.
- [7] Q. McCulloch, J.G. Gigax, P. Hosemann, Femtosecond Laser Ablation for Mesoscale Specimen Evaluation, JOM 72 (2020) 1694-1702.
- [8] J.G. Gigax, A.J. Torrez, Q. McCulloch, H. Kim, S.A. Maloy, N. Li, Sizing up mechanical testing: Comparison of microscale and mesoscale mechanical testing techniques on a FeCrAl welded tube, Journal of Materials Research 35 (2020) 2817-2830.
- [9] J.G. Gigax, H. Vo, Q. McCulloch, M. Chancey, Y. Wang, S.A. Maloy, N. Li, P. Hosemann, Micropillar compression response of femtosecond laser cut single crystal Cu and proton irradiated Cu, Scripta Materialia 170 (2019) 145-149.
- [10] J. Parker, In-service behaviour of creep strength ferritic steels Grade 91 and Grade 92 Part 2 weld issues. International Journal of Pressure Vessels and Piping 114-115 (2014) 76-87.
- [11] Z.Q. Fan, T. Hao, S.X. Zhao, G.N. Luo, C.S. Liu, Q.F. Fang, The microstructure and mechanical properties of T91 steel processed by ECAP at room temperature, Journal of Nuclear Materials 434 (1-3) (2013) 417-421
- [12] R.L. Klueh, Elevated temperature ferritic and martensitic steels and their application to future nuclear reactors, Int. Mater. Rev. 50 (2005) 287–310.
- [13] R.L. Klueh, A.T. Nelson, Ferritic/martensitic steels for next-generation reactors, J. Nucl. Mater. 371 (2007) 37–52.
- [14] B.P. Eftink, D.A. Vega, O. El-Atwani, D. J. Sprouster, J.S. Yoo, T. E. Steckley, E. Aydogan, C.M. Cady, M. Al-Sheikhly, T. J. Lienert, S.A. Maloy, Tensile properties and microstructure of additively manufactured Grade 91 steel for nuclear applications. Journal of Nuclear Materials 544 (2021).



References

- [15] O. El-Atwani, B. P. Eftink, C. M. Cady, D.R. Coughlin, M. M. Schneider, S. A. Maloy, Enhanced mechanical properties of additive manufactured Grade 91 steel, Scripta Materialia 199 (2021) 113888.
- [16] R.L. Klueh, J.M. Vitek, Tensile behavior of irradiated 12Cr-1MoVW steel, Journal of Nuclear Materials 137 (1) (1985) 44-50.
- [17] C. Xu, M. Hackett, TerraPower HT9 Mechanical and Thermal Creep Properties, Springer International Publishing, Cham, 2017.
- [18] C. Keller, Influence of the temperature on the tensile behaviour of a modified 9Cr-1Mo T91 martensitic steel, Materials Science and Engineering: A 527 (24) (2010) 6758-6764
- [19] Y. M. Wang and E. Ma, Three strategies to achieve uniform tensile deformation in a nanostructured metal, Acta Mater. 52 (2004) 1699-1709.
- [20] M.P. Echlin, M.S. Titus, M. Straw, P. Gumbsch, T.M. Pollock, Materials response to glancing incidence femtosecond laser ablation, Acta Mater. 124 (2017) 37-46.
- [21] Ridwan, Ridwan & Prabowo, Aditya & Muhayat, Nurul & Putranto, Teguh & Sohn, Jung-Min. (2020). Tensile analysis and assessment of carbon and alloy steels using FE approach as an idealization of material fractures under collision and grounding. Curved and Layered Structures. 7. 188-198.
- [22] Haroush, S & Priel, Elad & Moreno, Daniel & Bussiba, Arie & Silverman, Ido & Turgeman, A & Shneck, R & Gelbstein, Yaniv. (2015). Evaluation of the mechanical properties of SS-316L thin foils by small punch testing and finite element analysis. Materials and Design. 83. 75-84.

